

- Manual handling tips
- 01
- November 2023
- Localities Development Team

Good handling technique for lifting

Here are some practical tips, on safe manual handling.¹



Think before lifting/handling. Plan the lift. Can handling aids be used? Where is the load going to be placed? Will help be needed with the load? Remove obstructions such as discarded wrapping materials. For a long lift, consider resting the load midway on a table or bench to change grip.



Adopt a stable position. The feet should be apart with one leg slightly forward to maintain balance (alongside the load if it is on the ground). The worker should be prepared to move their feet during the lift to maintain their stability. Avoid tight clothing or unsuitable footwear, which may make this difficult.



Get a good hold. Where possible, the load should be hugged as close as possible to the body. This may be better than gripping it tightly with hands only.




- Manual handling tips
- 01
- November 2023
- Localities Development Team

Start in a good posture. At the start of the lift, slight bending of the back, hips and knees is preferable to fully flexing the back (stooping) or fully flexing the hips and knees (squatting).

Don't flex the back any further while lifting. This can happen if the legs begin to straighten before starting to raise the load.




Keep the load close to the waist. Keep the load close to the body for as long as possible while lifting. Keep the heaviest side of the load next to the body. If a close approach to the load is not possible, try to slide it towards the body before attempting to lift it.



Avoid twisting the back or leaning sideways, especially while the back is bent. Shoulders should be kept level and facing in the same direction as the hips. Turning by moving the feet is better than twisting and lifting at the same time.




- Manual handling tips
- 01
- November 2023
- Localities Development Team




Keep the head up when handling. Look ahead, not down at the load once it has been held securely.

Move smoothly. The load should not be jerked or snatched as this can make it harder to keep control and can increase the risk of injury.

Don't lift or handle more than can be easily managed. There is a difference between what people can lift and what they can safely lift. If in doubt, seek advice from a team member or get help.



Put down, then adjust. If precise positioning of the load is necessary, put it down first, then slide it into the desired position.



- Manual handling tips
- 01
- November 2023
- Document Owner: Localities Development Team

Good handling technique for pushing and pulling

Here are some practical points to remember when loads are pushed or pulled.

Handling devices. Aids such as barrows and trolleys should have handle heights that are between the shoulder and waist. Devices should be well maintained and wheels that run smoothly. The law requires that equipment should be maintained. When you buy new trolleys and so on, you must ensure that they are good quality with large diameter wheels made of suitable material with castors, bearings that will last with minimum maintenance.

Force. As a rough guide the amount of force that needs to be applied to move a load over a flat, level surface using a well-maintained handling aid is at least 2% of the load weight. For example, if the load is 400kg then the force needed to move the load is 8kg. The force needed will be larger, perhaps a lot larger, if conditions are not perfect (for example, wheels not in the right position or a device that is poorly maintained). The operator should try to push rather than pull when moving a load, provided they can see over it and control steering and stopping.

Slopes. Staff and volunteers should get help from a colleague whenever necessary, if using a slope or ramp, as pushing and pulling forces can be very high.

Uneven surfaces. Moving an object over soft or uneven surfaces requires higher forces. On an uneven surface, the force needed to start the load moving could increase to 10% of the load weight, although this might be offset to some extent by using larger wheels. Soft ground may even be worse.

Stance and pace. To make it easier to push or pull, staff and volunteer should keep their feet well away from the load and go no faster than walking speed. This will stop you becoming too tired too quickly.

¹ Information based on the Manual handling at work: A brief guide Health and Safety Executive INDG143 (rev3).